

# EcoWatt LiFePO4 Smart BMS 12.8V 100Ah

## ELECTRICAL PERFORMANCE

Nominal Voltage	12.8V
Nominal Capacity	100Ah
Capacity @ 20A	300min
Energy	1280Wh
Resistance	≤15 mΩ @ 50% SOC
Self Discharge	<3% / Month
Cells	Prismatic Cell 3.2V/100Ah
Application	12V installation, parallel connection only, no series connection
Number of Cycle	>4000 at 80% DoD



## DISCHARGE PERFORMANCE

Continuous Discharge Current	100A
Reconnect Voltage	>11.2V
Short Circuit Protection	1000-2000A ± 400A (200 ~ 800 μs)
Discharge Cut-Off Voltage	10V (2000 ms)
Peak Discharge Cut-Off Current	300A (200~500ms)

## MECHANICAL PERFORMANCE

Dimension (L x W x H)	330 x 172 x 215 mm
Weight	11.5 kg
Terminal Type	M8
Terminal Torque	80 ~ 100 in-lbs (9 ~ 11 N-m)
Case Material	ABS
Enclosure Protection	IP65
Extension	LCD Display

## CHARGE PERFORMANCE

Recommended Charge Current	20A
Maximum Charge Current	50A
Recommended Charge Voltage	14.6V
Reconnect Voltage	≤13.8V
Balancing Voltage	>12.8V

## TEMPERATURE PERFORMANCE

Discharge Temperature	-20 ~ 75 °C
Charge Temperature	0 ~ 50 °C
Storage Temperature	-5 ~ 35 °C

## COMPLIANCE

Warranty	2 Years
Shipping Classification	UN 3480, CLASS 9
Certifications	CE UN38.3 UL1642 & IEC621